

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/027970 A1

- (51) International Patent Classification⁷: **H02N 2/02**, B25J 9/10, A61F 2/08 (74) Common Representative: DANFOSS A/S; Patent Department, DK-6430 Nordborg (DK).
- (21) International Application Number: PCT/DK2003/000603 (81) Designated States (*national*): AM, AT, AU, BA, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HR, HU, IL, IN, IS, JP, KR, KZ, LT, LU, LV, MD, MK, MX, NO, NZ, PL, PT, RO, RU, SE, SG, SK, TR, UA, US, UZ, VN, YU, ZA.
- (22) International Filing Date: 18 September 2003 (18.09.2003) (84) Designated States (*regional*): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: PA 2002 01380 20 September 2002 (20.09.2002) DK
- (71) Applicant (*for all designated States except US*): DANFOSS A/S [DK/DK]; DK-6430 Nordborg (DK).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): BENSLIMANE, Mohamed Yahia [DZ/DK]; Egevej 76, DK- 6430 Nordborg (DK). GRAVESEN, Peter [DK/DK]; Hyldebærvej 6, DK-6430 Nordborg (DK).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: AN ELASTOMER ACTUATOR AND A METHOD OF MAKING AN ACTUATOR



(57) Abstract: A tubular elastomer actuator with a shape in a cross-sectional view which shape exposes at most one single axis of symmetry of a specific length, e.g. an oval shape. The actuator could be made from a sheet made from a plurality of plate shaped elements which are laminated together and rolled. Each plate shaped element may have a corrugation that gives the element an anisotropic structure, and contains an electrode on only one surface. The actuator displacement is the result of shrinkage displacement of the plate shaped elements upon the application of electrical field across their thickness.

WO 2004/027970 A1

Best Available Copy